

Quick Reference to Snackpoint Range Programming Menu

LIST OF PROGRAMME COMMANDS ACCESS TO SUBMENUS

Command 01 Machine test **Can be used to set number of spiral motors and to test and reset motors**

Command 02 Calls submenu for setting the clock & daily timers **Sets date and time**

Command 03 Recall of price setting submenu **Sets prices by selection, tray or whole machine**

11/12 ETC = SINGLE SELECTION

91 = SHELF 1

92 = SHELF 2 ETC

99 = ENTIRE MACHINE

Command 04 Calls submenu for setting discounted prices **Only used to discount food prices**

Command 07 Display of sales for full price selection **Audit display**

Command 08 Displays sales for selection discounted price **Audit display**

Command 09 Displays totals cashed not clearable **Audit display**

Command 10 Displays totals clearable **Clearable Audit totals**

TO SET REFRIGERATION PARAMETERS

Command 41 Sets cabinet temperature **Should be set t ...c**

Command 44 Sets defrost cycle frequency **N/A on snack only, only applicable on Duo**

Command 45 Setting the cut-out duration for the refrigeration safety device **Only applicable on Duo**

Command 46 Setting the trigger temperature for the refrigeration safety device **Only applicable on Duo**

Command 48 Setting trays with refrigeration safety device **Only applicable on Duo**

TO SET MACHINE PARAMETERS

Command 62 Enable discount

0 = no type of discount.

1 = discount for different time slots.

2 = discount for purchases with key /credit card (only possible in MDB mode).

3 = discount for time slots and for purchases with key /credit card (only possible in MDB mode)

Command 63 Set the mono/multivend **Default is 0 single vend**

Command 64 Sets the message display language **set to 1 for English**

Command 66-67 Internal temperature and evaporator temperature display

Displayed value

0 0 Displays clock

1 0 Displays internal temperature *

0 1 Displays internal temperature + evaporator temperature

1 1 Displays clock + internal temperature

MBD COIN SYSTEM

Command 69 Chooses functioning mode of the coin mechanism **Set to 5 for MBD**

The command 69 has to be programmed to value 5, then turn off the machine for some seconds. By putting it on again the machine and the coin mechanism will communicate correctly.

Command 30 Purchase obligation before return. **Set to 1 which means customer has to make a purchase**

Command 31 Setting max key or cash credit accepted. **Normally set at 10.00**

Command 32 Minimum coin level in the tubes. **Used to set change levels**

Command 33 Disabling single coins / banknotes **Used to disable certain coins**

Command 39 Filling of the change giving tubes.

1. Go into programming mode to display.....

2 Key in 39 and press B

3. Insert the coins in the coin mechanism

4. Press again the pushbutton B

Command 73 Enabling the photoelectric cells - Secure vend **set to 1 to enable**

Command 74 Photocell test - Secure vend **performs a test of all Photocells**

Command 93 Displays the temperature status over the last 24 hours **Use to check for temperature issues**

Command 94 Displays the last 10 power-offs **Use to check if Health control issues**

Command 99 View error events **Use to check error log refer to full manual for error codes**

