

COMMAND & ERROR CODES



Command Codes

OPERATOR COMMANDS

| #2 | DATE & TIME | Alarm set 01 - sets the year/month/day |
|-----|-------------------------|--|
| #3 | SETS PRICES | Type 03 and press ENTER to go to the price setting submenu. Drum number 00 - will appear on the display Enter the number of the drum for the price change - press ENTER Price appears on the display - enter new value and press ENTER to save it or ESC to return to main menu without saving |
| #9 | LIFETIME AUDIT | Displays totals dating back to Installation of machine. Available data: Total sold, Total in counter, Total in tubes, Total banknotes, Total given back, Total given out manually by the tubes, Total cashed overprice, Total discounted sales, Total sales with cashless system, Total sold with exact amount, Total cashed without sales, Number of sales carried out, Total value of the free-vends, Total number of the free-vends. |
| #10 | AUDIT DISPLAY | Daily Audit can be cleared. This command has the same functions as Command 09 - but can be cleared through Command 92 |
| #39 | FLOATS THE COIN MECH | 1. Programming mode, display views - Command 00 2. Input 39 and press # 3. Insert coins into the coin mechanism 4. Once finished press # again |
| #92 | CLEAR SALES DATA | Type 1221 and press ENTER |

Command Codes

COMMANDS TO ACCESS TO SUB-MENUS

| #1 | MACHINE TEST | Test delivery doors / drums + reset motors |
|-----|---------------|---|
| #2 | DATE & TIME | Enters sub-menu for setting the clock / daily timers / date |
| #3 | SETS PRICES | Price setting sub-menu / set drum prices / item prices |
| #7 | AUDIT DISPLAY | Display of sales for full price selection |
| #9 | AUDIT DISPLAY | Displays totals cashed not clear-able |
| #10 | AUDIT DISPLAY | Displays totals clear-able Can be cleared through #92 |

COMMANDS TO SET REFRIGERATION PARAMETERS

| #41 | SETS CABINET TEMPERATURE | Preset Value is +3°C |
|-----|--|--------------------------------------|
| #43 | END DEFROSTING TEMP SETTING | Preset Value is +5°C/DRIP TIME = 300 |
| #44 | SETS DEFROST CYCLE FREQUENCY | Preset Value is 3 Hours |
| #45 | SETS CUT-OUT DURATION FOR SAFETY | Preset Value is 60 minutes |
| #46 | SETS TRIGGER TEMP FOR SAFETY | Preset Value is +8°C |

Command Codes

COMMANDS TO SET MACHINE PARAMETERS

| #50 | SET DELIVERY DOOR SPEED & DRUM OPERATION | Preset Value is 60% (40% ÷ 95% of the max operating speed) |
|-----|--|--|
| #54 | SET DELIVERY DOOR OPENING TIME | Preset value is 5 seconds |
| #63 | SET THE SINGLE / MULTIVEND | Singlevend 0 / Multivend 1 |
| #64 | SETS DISPLAY LANGUAGE | Preset value is 1 for English |
| #66 | INTERNAL TEMPERATURE AND EVAPORATOR | The value set determines the info |
| #67 | TEMPERATURE DISPLAY | shown on 2nd line of display: |

| Command 66 | Command 67 | Displayed value |
|------------|------------|--|
| 0 | 0 | Displays clock |
| 1 | 0 | Displays internal temperature * |
| 0 | 1 | Displays internal temperature + evaporator temperature |
| 1 | 1 | Displays clock + internal temperature |

MBD COIN SYSTEMS + DRUM SET-UP

| #69 | FUNCTIONING MODE OF COIN MECH | SET TO 5 FOR MBD (SET #69 TO VALUE 5 - SWITCH OFF MACHINE - SWITCH ON AND COIN MECH COMMUNICATES WITH MACHINE) |
|--------|-------------------------------------|---|
| #71-80 | COMPARTMENT NUMBERS | 4,6,8,12,16,24,48 |
| #92 | CLEAR SALES DATA | Type 1221 and press ENTER |
| #99 | VIEW ERROR EVENTS | Use to check last 20 errors on log |

Error Codes

ERROR CODE MEANING

| 01 | DOOR NUMBER | Door does not open during sale |
|----|-------------|---|
| 02 | DOOR NUMBER | Door does not close (only command 01 Machine test) |
| 03 | DRUM NUMBER | Column tries to rotate drum with door open |
| 05 | DRUM NUMBER | Drum position time out |
| 07 | DRUM NUMBER | Column does not reach zero position |
| 08 | DRUM NUMBER | No drum encoder pulses |
| 10 | | Internal temp probe defective |
| 11 | | Evaporator probe defective |
| 16 | | Communication with power board blocked |
| 20 | | Delivery door not controllable |
| 21 | | Incorrect position parameter |
| 25 | DOOR NUMBER | Door does not open during reloading |
| 26 | DOOR NUMBER | Door does not close during reloading |

Error Codes

ERROR CODE MEANING

| 29 | DRUM NUMBER | Power board reset or the drum control card |
|----|-------------|--|
| 30 | | Fridge safety intervention |

RESET HEALTH CONTROL

THIS SHOULD ONLY BE RESET IF YOU ARE SURE THAT THE FRIDGE UNIT IS WORKING CORRECTLY!!

The cut-out duration for the refrigeration safety devices preset value is 60 minutes. If the fridge has not chilled down +5°C in 60 minutes then the Easy 6000 will go out with HEALTH CONTROL

TO RESET: Open Main door and press and hold the Blue Shopper Button